

Wind Mitigation Inspection Report



Property Address:

55/65/75/85 Woods Landing Trail Oldsmar, Florida 34677

Prepared For:

East Lake Woodlands Woods Landing

www.nealinspections.com



"Inspected once, Inspected right" "

www.Nachi.org





Neal Inspections LLC nealinspections@gmail.com



Troy Neal: (813) 545-5363 William Neal: (813) 352-4690

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

| Inspecti | Inspection Date: 2/07/2024 | | | | | | | |
|--|---|--|--|--|--|--|--|--|
| Inspection Date: 3/07/2024 Owner Information | | | | | | | | |
| | Name: East Lake Woodland | Contact Person: Roya | Contact Person: Beverly | | | | | |
| | 55/65/75/85 Woods Land | | | | Sily | | | |
| | Oldsmar | | | | Home Phone: Work Phone: | | | |
| | Pinellas | F. | 21p. 34077 | | Cell Phone: | | | |
| | ce Company: | 1 | | Policy #: | | | | |
| | | # of Stories: Two | # of Stories: T | | Email: bneubecker@ameritechmail.com | | | |
| | | | | | | | | |
| NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form. | | | | | | | | |
| the | 1. Building Code : Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)? | | | | | | | |
| | A. Built in compliance with the a date after 3/1/2002: Building | | | lt in 2002/2003 provide a peri | mit application with | | | |
| | B. For the HVHZ Only: Built is provide a permit application w | in compliance with the SFI | BC-94: Year Built | For homes built in 19 | | | | |
| | C. Unknown or does not meet | | | ` | | | | |
| OR | Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified. | | | | | | | |
| | 2.1 Roof Covering Type: | Permit Application Date | FBC or MDC Product Approval # | Year of Original Installation or Replacement | No Information Provided for Compliance | | | |
| | ✓ 1. Asphalt/Fiberglass Shingle | 2/01/2013 | | | | | | |
| | 2. Concrete/Clay Tile | | | | П | | | |
| | 3. Metal | | | | $\overline{\Box}$ | | | |
| | 4. Built Up | | | | $\overline{\Box}$ | | | |
| | 5. Membrane | | | | Ä | | | |
| | 6. Other | | | | | | | |
| _ | | | | | | | | |
| _ | A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. | | | | | | | |
| | B. All roof coverings have a M | | | | | | | |
| _ | roofing permit application afte | | | • | ater. | | | |
| | C. One or more roof coveringsD. No roof coverings meet the | | | OFB. | | | | |
| | _ | _ | | | | | | |
| | f Deck Attachment: What is t | | | | 60 m: 1 | | | |
| _ | A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below. | | | | | | | |
| _ | B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of | | | | | | | |
| | 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, | | | | | | | |
| | other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance 8d nails spaced a | | | | | | | |
| | maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf. C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of | | | | | | | |
| | 24"inches o.c.) by 8d commor decking with a minimum of 2 Any system of screws, nails, a | nails spaced a maximum nails per board (or 1 nail p | of 6" inches in the fi er board if each board | ieldOR- Dimensional lumb rd is equal to or less than 6 ir | er/Tongue & Groove aches in width)OR- | | | |
| | Inspectors Initials TN Property Address 55/65/75/85 Woods Landing Trail 34677 | | | | | | | |
| | | | | | | | | |

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 1 of 4

| | | or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at leas 182 psf. D. Reinforced Concrete Roof Deck. | | | | | |
|-------------|---------------|--|-------------------|--|--|--|--|
| ☐ E. Other: | | | | | | | |
| | | | | or unidentified. | | | |
| | Ш | G. | No attic a | ccess. | | | |
| 4. | | et o | of the inside | achment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within e or outside corner of the roof in determination of WEAKEST type) | | | |
| | | | | Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or | | | |
| | | | | Metal connectors that do not meet the minimal conditions or requirements of B, C, or D | | | |
| | Mir | iim | al conditio | ons to qualify for categories B, C, or D. All visible metal connectors are: | | | |
| | 1111 | | | Secured to truss/rafter with a minimum of three (3) nails, and | | | |
| | | | ✓ | Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. | | | |
| | ✓ | В. | Clips | | | | |
| | | | | Metal connectors that do not wrap over the top of the truss/rafter, or Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails. | | | |
| | | C. | Single Wi | Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. | | | |
| | | D. | Double W | •• • | | | |
| | | | | Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or | | | |
| | | | | Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. | | | |
| | | F. | Structural Other: | | | | |
| | \sqsubseteq | G. Unknown or unidentified | | | | | |
| | Ш | Η. | No attic a | ccess | | | |
| 5. | | | | What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). | | | |
| | | A. | Hip Roof | | | | |
| | | В. | Flat Roof | Total length of non-hip features: feet; Total roof system perimeter: feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft | | | |
| | √ | C. | Other Roo | | | | |
| 6. | | condary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined. | | | | | |
| Ins | spec | tor | s Initials T | N Property Address 55/65/75/85 Woods Landing Trail 34677 | | | |
| *T | hic v | æri | ification fo | orm is valid for un to five (5) years provided no material changes have been made to the structure or | | | |

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart

| Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings. | | Glazed Openings | | | | Non-Glazed Openings | |
|--|--|------------------------------|-----------------|-----------|----------------|------------------------|-----------------|
| | | Windows or Entry Doors | Garage Doors | Skylights | Glass Block | Entry Doors | Garage Doors |
| N/A | Not Applicable- there are no openings of this type on the structure | | | | | | |
| Α | Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) | | | | | | |
| В | Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) | | | | | | |
| С | Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 | | | | | | |
| D | Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance | | | | | | |
| NI . | Opening Protection products that appear to be A or B but are not verified | | | | | | |
| N | Other protective coverings that cannot be identified as A, B, or C | | | | | | |
| Х | No Windborne Debris Protection | X | | | | | |
| system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). • Miami-Dade County PA 201, 202, and 203 | | | | | | | |
| | Florida Building Code Testing Application Standard (TAS) 20 | 01, 202, <u>and</u> | 203 | | | | |
| American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 | | | | | | | |
| Southern Standards Technical Document (SSTD) 12 | | | | | | | |
| | For Skylights Only: ASTM E 1886 <u>and</u> ASTM E 1996 | | | | | | |
| | For Garage Doors Only: ANSI/DASMA 115 | | | | | | |
| A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist | | | | | | | |
| A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above | | | | | | | |
| A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above | | | | | | | |
| B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): • ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.) | | | | | | | |
| | • SSTD 12 (Large Missile – 4 lb. to 8 lb.) | | | | | | |
| _ | • For Skylights Only: ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile - 2 to 4.5 lb.) | | | | | | |
| | B.1 All Non-Glazed openings classified as A or B in the table above, or no N | | | | | | |
| _ | B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above | | | | | | |
| | B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the | e table abov | e | | | | |
| C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). | | | | | | | |
| C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist | | | | | | | |
| C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above | | | | | | | |
| C.3 One or More Non-Glazed openings is classified as Level N or X in the table above | | | | | | | |

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

Inspectors Initials TN **Property Address** 55/65/75/85 Woods Landing Trail

34677

| N. Exterior Opening Protection (unverified shutter protective coverings not meeting the requirements of with no documentation of compliance (Level N in the | Answer "A", "B", or C" or sy | | | | |
|--|--|---|--|--|--|
| <u> </u> | · | In Clared arrainer suist | | | |
| | N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist N.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level X in the | | | | |
| N.3 One or More Non-Glazed openings is classified as L | evel X in the table above | | | | |
| X. None or Some Glazed Openings One or more Glazed | | Level X in the table above. | | | |
| MITIGATION INSPECTIONS MUST Section 627.711(2), Florida Statutes, pr | _ | | | | |
| Qualified Inspector Name: Troy Neal | License Type: Home Inspector | License or Certificate #: HI-10032 | | | |
| Inspection Company: | <u> </u> | Phone: | | | |
| Neal Inspections LLC | | 813-545-5363 | | | |
| Qualified Inspector – I hold an active license as a: (check one) ✓ Home inspector licensed under Section 468.8314, Florida Statutes who has completed the statutory number of hours of hurricane mitigation training approved by the Construction Industry Licensing Board and completion of a proficiency exam. ☐ Building code inspector certified under Section 468.607, Florida Statutes. ☐ General, building or residential contractor licensed under Section 489.111, Florida Statutes. ☐ Professional engineer licensed under Section 471.015, Florida Statutes. ☐ Professional architect licensed under Section 481.213, Florida Statutes. | | | | | |
| Any other individual or entity recognized by the insurer as pos- verification form pursuant to Section 627.711(2), Florida Statu | | ons to properly complete a uniform mitigation | | | |
| Individuals other than licensed contractors licensed under Section 489.111, Florida Statutes, or professional engineer licensed under Section 471.015, Florida Statues, must inspect the structures personally and not through employees or other persons. Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and experience to conduct a mitigation verification inspection. I, | | | | | |
| <u>Homeowner to complete</u> : I certify that the named Qualified Inspector or his or her employee did perform an inspection of the residence identified on this form and that proof of identification was provided to me or my Authorized Representative. | | | | | |
| Signature: Date: | | | | | |
| | | | | | |
| An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes) | | | | | |
| The definitions on this form are for inspection purposes as offering protection from hurricanes. | only and cannot be used to c | ertify any product or construction feature | | | |
| Inspectors Initials TN Property Address 55/65/75/85 Woods Landing Trail 34677 | | | | | |
| *This verification form is valid for up to five (5) years prinaccuracies found on the form. | ovided no material changes | have been made to the structure or | | | |

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155



55/65/75/85 Woods Landing Trail 34677



Side Elevation



8d Ringshank Renail



Rear




Side Elevation



8d Nails within 6"



Clips observed



Roof Permit PER-H-CW13-00795 (2/01/2013) with SWR

